

# MODEL 200UC

## 12" Capacity Hand-Fed Chipper

The Model 200UC is for professionals focused on trimming, yet it is rugged enough to chip 12" diameter material. It's particularly popular with utility line and right-of-way contractors because of its maneuverability and cost-effective performance. Its compact design makes the Model 200UC easy to tow and position, and its feed rate of 120 feet per minute quickly converts large quantities of brush into dimensional chips. Gasoline and diesel engine options from 49 to 130 horsepower will keep the crew busy feeding and Bandit's solid-weld construction will provide years of dependable service, with many 200UC's remaining on front-line service for over a decade.

### COMPACT CHIPPER, BIG APPETITE.

- 17 1/2" wide chipper opening easily processes large material
- Powerful dual-wheel horizontal feed system crushes and compresses limbs, reducing trimming time
- Compact and maneuverable with high production capacity is ideal for rental companies serving both homeowners and contractors.



### Reduce Your Labor Costs

The powerful dual-wheel feed system consists of two spring tensioned 17" wide X 17-1/2" diameter feed wheels, mounted in Bandit's proven slide box system. With 1600 pounds of pulling force from each feed wheel, the 200UC effectively pulls trees and large limbs into the chipper. Material is folded and crushed with **little-to-no extra trimming, repositioning or cutting larger pieces into shorter lengths**. The sloping infeed tray makes it quicker and easier to load and slide brush, logs and trees into the feed system.

### Reduce Your Transportation Costs

No other hand-fed chipper throws harder than a Bandit. The proprietary design of Bandit throwers, chipper transitions and discharge chutes aggressively throw material by minimizing chip resistance. A standard 360-degree hand-crank swivel discharge with chip deflector fully loads chip boxes, **reducing trips to the dump site**. The throwing power also increases the chipping broadcast area for projects where chips are left on site.

### Produce A Marketable Chip

Bandit's synchronized feed system feeds material at the rate the chipper wants to chip it. Wood is never held from nor forced against the disc. This reduces wear to the disc, prolongs knife life, and produces a consistent, uniform chip that's far more marketable.

Bandit owners get paid for their chips while companies running other chippers often are forced to pay for chip disposal. Even with recycling requirements for materials increasing, **Bandit chippers produce valuable chips** used in biomass energy and mulch applications. Bandit chips are also used for erosion control on embankments and in erosion socks for construction projects.



# Bandit

## INDUSTRIES, INC.

6750 Millbrook Rd. • Remus, MI 49340 • 1-800-952-0178

FIND US ONLINE     [WWW.BANDITCHIPPERS.COM](http://WWW.BANDITCHIPPERS.COM)

# Model 200UC

12" Capacity Disc-Style Chipper

## Extremely Easy To Service and Maintain

Bolt-in knives are easy to access and change through the chipper hood. The knives are reversible with two usable edges per sharpening. Knives can be sharpened up to five or six times before replacement. All grease points are easy to reach, and all other service areas are easy to access.



## Safety Features

- **Rope/Line Shear Device** (standard)  
Provides an improved chance that rope or lines inadvertently entering the chipper may be cut.
- **Last Chance Cables** (standard)  
Reverses the infeed rollers when pulled in case of an emergency.
- **Operator Safety Control Bar** (standard)  
Wraps around three sides of the infeed chute and controls the direction of the feed wheels.
- **Wood Pusher Paddle** (standard)  
Used to feed small wood debris into the chipper.
- **Chipper Hood Pin /W Padlock** (standard)  
Prevents unauthorized access to the disc or drum.
- **Chipper Hood Engine Disable Plug** (standard)  
Prevents engine from being started without the hood pin in place.
- **Feed Wheel Engage** (option)  
Requires operators to control feed wheel operation via foot pedal.
- **Hydraulic Bump Bar** (option)  
Stops feed wheels via mechanical connection when bumped, diverting hydraulic power away from the feed wheels.

## We Are Here To Support You

There are nearly 200 dealer locations in the US and 61 international dealers to support you. They are factory trained. Plus we have an experienced parts and service department supporting you and our dealers.



OPTIONAL PTO DRIVE

## Model 200UC Specifications

### ENGINES

**TOWABLE:**

- 89 HP Gas
- 130 HP Gas
- 49.4 HP Diesel
- 74 HP Diesel

### UNDERCARRIAGES

**TOWABLE:**

**AXLE** - Single 6,000 pound Torflex EZ-lube axle  
**TIRES** - (2) 225/75R 15" tires mounted on 6-bolt white spoke rims

### MEASUREMENTS:

**TOWABLE:**

**Length:** 14'  
(Infeed Closed)  
**Length:** 16' 6"  
(Infeed Open)  
**Width:** 6'  
**Height:** 8'  
**Weight:** 4,500 lbs  
**Fuel Tank:** 24-1/2 gal  
**Hyd. Tank:** 12 gal


### OTHER SPECIFICATIONS:

**Capacity:** 12"  
**Throat Opening:** 14" x 17"  
**Disc:** 40" diameter x 1 1/4" thick  
with 1-1/2" thick hub  
**RPM:** 1,150  
**Feed System:** Slide box  
**Adjustable Springs:** 2 - 17"  
**Horizontal feed wheels:** 2  
**Displacement (CID):** 15.9 CID  
**Hydraulic Motors:** 2  
**Wheel Thickness:** 40" diameter x 1-1/4"  
Two knife pockets  
**Discharge:** 360° Manual Swivel  
**Deflector:** 3-Position Manual  
**Hitch:** 2 Position, 2-1/2" Pintle  
**Frame:** 3/16" x 2" x 6" main frame  
with a 1/4" x 3" x 6" tongue  
**Tongue Jack:** 5,000 pound "Bulldog" tongue  
jack, adjustable for height with  
15" travel capacity and stationary foot pad



## Paint Colors

Choose from six standard colors, or select a custom color to match your fleet.



BANDIT YELLOW    ALERT ORANGE    CAT YELLOW    GREEN    BLACK    WHITE